Autoclaves

Benchtop Autoclaves, LTE Mediclave

A comprehensive range of front loading, benchtop autoclaves complying with EU Directives 93/42/EC, EN13060, 97/23/EC, EN61326-1, EN61010-1 and EN61010-2-40.

- Choice of chamber size:
 6 litre: 236 x 301.5mm diameter x depth
 - 18 litre: 236 x 381.5mm diameter x depth
 - 23 litre: 236 x 530mm diameter x depth
- 121°C or 134°C cycles available with up to 12 programme options
- Choice of operational class:
 - B: fractionated vacuum for solid and hollow instruments, wrapped instruments and porous loads with up to four vacuum pulses
 - S: Pre- and post-cycle vacuum for solid or wrapped instruments and small porous loads
 - N: non-vacuum, thermodynamic for solid instruments only
- One-piece, stainless steel chamber vessel
- Separate steam generator produces steam rapidly, reducing cycle times and means that there are no heating elements within the chamber
- The motorised door has no bolts or levers; door locking at the start of the cycle and release at the end is fully automatic
- Integral supply and waste tanks with quick connections for easy filling (requires deionised water) or draining and sensors to monitor levels and warn if empty or full
- Integral data printer with accessory USB datalogger available

Chamber capacity,	litres	6	18	23
Chamber dimensions,				
dia. x depth	mm	236 x 301.5	236 x 381.5	236 x 530
Programmes,	class B*	11	11	11
	class S*	-	11	11
	class N	-	5	5
Trays supplied x size,	mm	1 x 19 x 150 x 250	4 x 17 x 185 x 285	4 x 17 x 185 x 440
		2 x 19 x 115 x 240	-	_
Supply requirements		220-240V 50/60Hz singl	e phase - all models	
Overall H x W x D	mm	345 x 445 x 610	400 x 505 x 610	400 x 505 x 695
Weight, kg	class B	25	45	50
	class S	-	40	45
	class N	-	35	40

^{*} Vacuum models have an additional vacuum test cycle.

As described, supplied with integral printer and trays as indicated. For 220-240V 50/60Hz single phase supplies, 2.5kW.

AU133-05	MED/06/B, 6 litres, class B
AU133-10	MED/18/B, 18 litres, class B
AU133-20	MED/23/B, 23 litres, class B
AU133-25	MED/18/S, 18 litres, class S
AU133-40	MED/23/S, 23 litres, class S
AU133-45	MED/18/N, 18 litres, class N
AU133-50	MED/23/N, 23 litres, class N

Accessories and spares

AU134-02 USB datalogger

TST indicator strips, 121°C/15 minutes and 134°C/3.5 minutes. Box of 100. AU127-29

DB105-10 Deioniser, Elga B114

AU134-08 Spare thermal paper roll for integral

printer







