

Bags

Sample Bags

All dimensions are nominal.

Sample, plain

Polyethylene, lightweight. Supplied in packs of approximately 100.

	Size mm
BA055-20	100 x 150
BA055-34	150 x 200
BA055-47	200 x 350
BA055-52	250 x 375

Bag Ties

Plastic covered wire 150mm long for closing bags. Supplied in packs of 1000.

BA095-15 Bag ties

Sample, reseal

Polyethylene. With rim-channel closure, which can be opened and resealed repeatedly. Supplied in bags of 100.

	Size mm
Plain	
BA100-19	80 x 120
BA100-33	100 x 150
BA100-39	120 x 170
BA100-51	200 x 300
BA100-56	300 x 400

With writing panel

BA102-16	70 x 100
BA102-33	100 x 150
BA102-39	120 x 170
BA102-51	300 x 400

Biohazard Sample Bags

Clear polyethylene, with grip seal, rim-channel closure and printed with symbol. Supplied with dimensions as indicated and in packs of 1000.

BA103-10	140 x 150mm
BA103-15	225 x 150mm



BA055 with BA095



BA100 in use

Sealing Film and Sealers

Nylon sealing film

- ◆ Resistant to bacterial contamination, heat, oils and greases
- ◆ Maintains sterility of wrapped item for long periods after autoclaving
- ◆ Non-toxic, odourless and tasteless

A non-toxic, elastic nylon film which is ideal for most packaging applications. Working temperature range -70 to +180°C. Permeable to steam allowing use as a wrapping for autoclaving. Available in a variety of layflat widths to accommodate various item shapes and sizes. Thickness 0.05mm (Gauge C). Supplied in a roll of 30 metres.

	Approx. layflat width, mm
SE162-13	25
SE162-16	50
SE162-19	75
SE162-21	100
SE162-24	125
SE162-27	150
SE162-30	200
SE162-33	250
SE162-36	300
SE162-42	500



BA102 in use



SE162



BA103



TS400-30, TS400-20 is similar

Impulse Heat Sealers

For heat sealing polyethylene film and other low melting point plastics, metallised film laminates etc. With hand operated hinged sealing bar and automatic control for adjusting the weld time. Will seal film up to 250 microns thick (1000 gauge). For 220-240V 50Hz single phase supplies.

Single timer model

TS400-20 Seal length 230mm

Dual timer model

Provides additional control of the cooling part of the weld cycle. Includes also a cutter for layflat tubing.

TS400-30 Seal length 300mm