

Balances

Portable Electronic Balances Scout® STX Series

OHAUS®

Highly featured, versatile balances for laboratory and industrial applications.

- ◆ Battery or mains operation
- ◆ Capacities up to 8200g maximum
- ◆ Full range tare
- ◆ Weigh-below facility
- ◆ User selectable units g, mg, kg, ct, N, oz, ozt, dwt, lb, lb:oz, gm, tl, tc, tla, custom
- ◆ Application modes: weighing, % weighing, parts counting, check weighing, dynamic/animal weighing, totalisation, density determination, Mole weighing, display hold
- ◆ Full colour, touchscreen WQVGA display with QWERTY keyboard and numeric keypad input
- ◆ Choice of accessory USB, RS232, Bluetooth® or ethernet interfaces
- ◆ Features include: level indicator and adjustable feet, menu lock switch, stability, overload and underload indicators, auto shut-off for battery saving
- ◆ Impact resistant plastic case with stainless steel pan

As described. Supplied with weigh-below hook and a.c. mains adapter (Models up to 620g are also supplied with calibration weight). Without batteries (4 x 1.5V AA required). Overall 202 x 224 x 54mm W x D x H (except 120g and 220g models with draught shield which are 103mm high. Weight 1kg. A 240V 50/60Hz a.c. single phase supply is required for the adapter.

	Model	Capacity g	Readability g	Pan size mm
BB540-62	STX123	120	0.001	93 diameter
BB540-64	STX223	220	0.001	93 diameter
BB540-67	STX222	220	0.01	120 diameter
BB540-71	STX422	420	0.01	120 diameter
BB540-74	STX421	620	0.1	120 diameter
BB540-78	STX621	620	0.1	170 x 140
BB540-81	STX1202	1200	0.01	170 x 140
BB540-86	STX2201	2200	0.1	170 x 140
BB540-89	STX6201	6200	0.1	170 x 140
BB540-94	STX8200	8200	1.0	170 x 140

Accessories

- BL610-15** Battery 1.5V, AA (4 required)
- BL542-20** USB device interface kit for connecting the balance to the user's computer
- BL542-24** RS232 interface kit
- BL542-28** Bluetooth® interface kit
- BL542-32** Ethernet interface kit

Dot matrix printer, SF40A

With paper rolls, RS232 cable, adapter, ribbon and mains adapter for 100-240V 50/60Hz supplies.

- BB528-14** Printer SF40A
- BB528-28** Paper rolls for BB528-14, pack of 2
- BB528-29** Ink ribbon cassette for BB528-14, pack of 1
- BD722-28** Calibration weight, OIML class M2, 1kg for BB540-81 and BB540-86
- BD722-30** Calibration weight, OIML class M2, 2kg for BB540-86, BB540-89 and BB540-94



BB540-67 to -74



BB540-62 to -64



BB540-78 to -94