

# Balances

## Portable Electronic Balances, Compass CX/CR Series

### OHAUS®

- ◆ Battery or mains (using accessory adapter) operation
- ◆ Choice of models:
  - CX: with stainless steel pan, 128 x 142mm and g, N, oz, lb:oz units
  - CR: with plastic pan, 125 x 132mm and g, ozt, dwt, lb:oz units
- ◆ Large LCD readout (backlit: CX-models only)
- ◆ Full subtractive tare

Overall 135 x 201 x 41mm W x D x H, weight 0.5kg (CX-models), 140 x 205 x 41mm, 0.4kg (CR-models). Supplied with 3 x 1.5V AA batteries.

|                 | Model  | Capacity<br>g | Readability<br>g |
|-----------------|--------|---------------|------------------|
| <b>BB557-10</b> | CX221  | 220           | 0.1              |
| <b>BB557-15</b> | CX621  | 620           | 0.1              |
| <b>BB557-20</b> | CX1201 | 1200          | 0.1              |
| <b>BB557-25</b> | CX2200 | 2200          | 1.0              |
| <b>BB557-30</b> | CX5200 | 5200          | 1.0              |
| <b>BB559-10</b> | CR221  | 220           | 0.1              |
| <b>BB559-15</b> | CR621  | 620           | 0.1              |
| <b>BB559-25</b> | CR2200 | 2200          | 1.0              |
| <b>BB559-30</b> | CR5200 | 5200          | 1.0              |

#### Accessories

- BB552-26** Container, plastic, capacity approx. 1050ml
- BB557-90** Mains adapter with UK plug for CX-models only. Requires a 230V 50/60Hz a.c. single phase supply
- BB559-85** Mains adapter with UK plug for CR-models only. Requires a 230V 50/60Hz a.c. single phase supply
- BL610-15** Spare battery 1.5V, AA (3 required)

Calibration weights to OIML class M2.

- BD722-22** 100g
- BD722-28** 1kg
- BD722-30** 2kg



BB557



BB559