

Balances

Portable Electronic Balances CS/CS-E Series

OHAUS®

- ◆ Mains or battery operation
- ◆ Choice of models:
 - CS: with removable stainless steel pan, batteries and a.c. adapter
 - CS-E with plastic pan and batteries only (accessory mains adapter available)
- ◆ Easy to read, 11mm high, LCD readout
- ◆ Choice of g or oz weighing modes
- ◆ Full subtractive tare

Overall 193 x 135 x 39mm W x D x H. Weight 0.55kg (CS-), 0.47kg (CS-E). With oval pan 146 x 133mm L x W and 3 x 1.5V AA batteries with auto shut-off after 5 minutes without use. CS- models are additionally supplied with a mains adapter for 240V 50/60Hz a.c. single phase supplies.

	Model	Capacity g	Readability g
BB550-66	CS200	200	0.1
BB550-72	CS2000	2000	1.0
BB550-77	CS5000	5000	1.0
BB550-80	CS200E	200	0.1
BB550-85	CS2000E	2000	1.0
BB550-90	CS5000E	5000	1.0

Accessories and spares

- BB542-10** Mains adapter. For 240V 50/60Hz a.c. single phase supplies
- BB552-26** Container, plastic, capacity approx. 1050ml
- BB552-28** Pan cover, stainless steel
- BL610-15** Spare battery 1.5V, AA (3 required)

Calibration weights to OIML class M2.

- BD722-22** 100g for BB550-66/-80
- BD722-28** 1kg for BB550-72/-85
- BD722-30** 2kg for BB550-77/-90



BB550-66/BB550-77



BB550-80/BB550-90

Heavy Duty Electronic Balances Catapult 5000 C51XE Series

OHAUS®

- ◆ Low-profile, heavy duty, rugged balances for weighing up to 200kg
- ◆ User selectable units kg, g, lb, oz
- ◆ Easy to read 20mm high LED readout
- ◆ 3-way mounting bracket allows the indicator to be mounted on or above the platform base, or on a wall
- ◆ Four button operation
- ◆ Mains or battery operation using accessory, rechargeable, 6V 4Ah lead acid battery

Supplied with indicator mounting bracket, stainless steel platform and a.c. mains adapter. A 240V 50/60Hz a.c. single phase supply is required for the adapter.

	Model	Capacity kg	Readability g	Platform size, mm
BB560-14	C51XE6R	6	2	310 x 270
BB560-21	C51XE30R	30	10	310 x 270
BB560-26	C51XE50R	50	20	310 x 270
BB560-36	C51XE50L	50	20	520 x 400
BB560-48	C51XE100L	100	50	520 x 400
BB560-58	C51XE200L	200	100	520 x 400

Accessories

- BB564-08** Rechargeable lead-acid battery, 6V 4Ah, for C51XE-series balances

Dot matrix printer, SF40A

Multifunction, dot matrix printer with statistics, and totalisation functions, date, time and GLP/GMP-compliant printout on non-fading, temperature-resistant paper. Up to 10 print languages can be selected. Supplied with RS232C interface cable, software and adapter to fit Ohaus laboratory balances, paper roll, ribbon cartridge and a.c. adapter for 100-240V 50/60Hz a.c.

- BB528-14** Printer SF40A
- BB528-28** Paper rolls for BB528-14, pack of 5
- BB528-29** Ink ribbon for BB528-14, pack of 1



BB560-14/BB560-26



BB560-36/BB560-58