

Balances

Explorer Series, Semi-Micro Analytical Balances

OHAUS®

- ◆ Brilliant, backlit, high resolution, VGA, touchscreen display programming
- ◆ Multiple application modes and user application setting library
- ◆ Application modes:
 - Parts counting
 - Check weighing
 - Filling
 - Pipette adjustment
 - Totalisation
 - Differential weighing
 - Ingredient costing
 - Dynamic weighing
 - Percentage weighing
 - Gross-Net-Tare
 - Density determination
 - Formulation
 - Peak hold
 - Under/over filling
- ◆ Internal autocalibration, with temperature and time-sensitive initialisation
- ◆ Built-in ioniser to eliminate static electricity around the sample
- ◆ 11 language display text options, including: English, Spanish, French, German and Italian
- ◆ GLP and GMP compliant outputs through USB or RS232 ports
- ◆ Touchless operation sensors (-/AD models also have automatic door opening, triggered via front and side sensors or a touchscreen button)
- ◆ Detachable display/control module for remote use (cable included)

Model	EX125D	EX125	EX225D	EX225D/AD	EX225/AD
Capacity	g 52/120	120	120/220	120/220	220
Readability	mg 0.01/0.1	0.01	0.01/0.1	0.01/0.1	0.01
Weighing modes	g, mg, oz, ozt, ct, dwt, tael, mo, gn, ti, N, custom units - all models				
Pan size	mm 80 diameter - all models				
Height above pan	mm 220 - all models				
Stabilisation time	seconds <3 - 0.1mg readability, <8 - 0.01mg readability				
Dimensions, W x D x H	mm 230 x 350 x 393 - all models				
Weight	kg 7	7	7	7.5	7.5

Explorer Series Semi-Micro Balances

As described. With high resolution, backlit, colour dot matrix touchscreen display, with protective in-use cover, 500mm extension cable for detachable module, RS232 and USB interfaces and a.c. adapter for 100-240V 50/60Hz single phase supplies.

- BB608-10** Model EX125D
- BB608-20** Model EX125
- BB608-30** Model EX225D
- BB608-40** Model EX225D/AD
- BB608-40** Model EX225/AD

Accessory dot matrix printer, SF40A

Multifunction, dot matrix printer with statistics, and totalisation functions, date, time and GLP/GMP-compliant printout on non-fading, temperature-resistant paper. Up to 10 print languages can be selected. Supplied with RS232C interface cable, software and adapter to fit Ohaus laboratory balances, paper roll, ribbon cartridge and a.c. adapter for 100-240V 50/60Hz a.c.

- BB528-14** Printer SF40A
- BB528-28** Paper rolls for BB528-14, pack of 5
- BB528-29** Ink ribbon for BB528-14, pack of 1

EC Type Approved versions are available - details on request.



BB608



BB528-14