

Voyager Pro Series Precision Top Loading Balances

OHAUS®

- ◆ High resolution, back-lit graphics LCD with adjustable intensity
- ◆ Cursor selection keys for ease of use
- ◆ Bi-directional RS232 interface and remote/auxiliary port for use with accessory remote display or tower mount kits
- ◆ Parts counting, statistics, differential weighing, formulation, check weighing, animal weighing, pipette calibration and density functions
- ◆ Full range tare
- ◆ Selectable stability levels and filters
- ◆ Weigh-below facility
- ◆ AutoCal™ automatic internal calibration prompted by ambient temperature fluctuation outside the range allowing accuracy to be maintained
- ◆ Applications library used to store and rapidly recall past procedures with up to five hundred steps memorised
- ◆ GLP protocol functions
- ◆ Five display text language options: English, Spanish, French, German and Italian
- ◆ Ergonomic levelling system

Model		VP213C	VP413C	VP413DC*	VP612C
Capacity	g	210	410	100/410	610
Readability	g	0.001	0.001	0.001/0.01	0.01
Weighing modes		g, mg, kg, lbs, oz, ozt, ct, dwt, taels, mo, gn, ti, N, custom — all models			
Pan size	mm	120 dia.	120 dia.	120 dia.	172 x 172
Dimensions W x L x H	mm	210 x 350 x 103	210 x 350 x 103	210 x 350 x 103	210 x 350 x 103
Weight	kg	6	6	6	5

*With moveable fine range allowing higher readability to be accessed at any point in the overall capacity.

Model		VP4102C	VP4101C	VP6100C	VP8101C
Capacity	g	4100	4100	6100	8100
Readability	g	0.01	0.1	0.1	0.1
Weighing modes		g, mg, kg, lbs, oz, ozt, ct, dwt, taels, mo, gn, ti, N, custom — all models			
Pan size	mm	172 x 172	172 x 172	172 x 172	172 x 172
Dimensions W x L x H	mm	215 x 350 x 103	215 x 350 x 103	215 x 350 x 103	215 x 350 x 103
Weight	kg	5	5	5	5

Voyager Pro Top Loading Balances

As described. With high resolution back-lit graphics LCD, bi-directional RS232 interface and a.c. adapter for 100-120, 220-240V 50/60Hz single phase supplies.

BB638-50 Model VP213C
BB638-54 Model VP413C
BB638-60 Model VP413DC
BB638-65 Model VP612C

BB638-70 Model VP4102C
BB638-75 Model VP4101C
BB638-80 Model VP6101C
BB638-85 Model VP8101C

Accessories

Impact printer, CBM-910

With paper rolls, ribbon and mains adapter for 230V 50/60Hz supplies. Requires printer cable kit adapter for connection to balances with RS232 output only.

BB528-10 Printer CBM-910
BD166-48 Paper rolls for BB528-10, pack of 5
BB528-24 Ink ribbon cassette for BB528-10, pack of 1
BB605-95 Printer cable kit 1 for connecting BB638 balances to BB528-10 printer

EC Type Approved versions are available – details on request.



BB638