

Balances

Defender™ 3000 Bench Scale Balances

OHAUS®

- ◆ Selectable weighing units: kg, g, lb, oz, lb:oz
- ◆ Parts counting mode with selectable samples sizes: 5, 10, 20, 50, 100 piece, with memory of last sample size and weight
- ◆ Rugged construction with tubular, painted carbon steel frame, aluminium loadcell protected to IP67 and Grade 304 stainless steel platform
- ◆ Adjustable non-slip rubber levelling feet with external level indicator
- ◆ ABS indicator housing and backlit, high-resolution LCD readout with 25mm high digits
- ◆ Stabilisation time: 2 seconds
- ◆ Fitted with bidirectional RS232 interface
- ◆ Span capacity 5lb/kg to 100% capacity
- ◆ Internal rechargeable lead acid battery and a.c. adapter
- ◆ Additional features include auto-off for battery power conservation, auto-zero tracking, environmental filtering and gravitational force adjustment

Model		D31 P30BR	D31 P60BR	D31 P60BL	D31 P150BL
Capacity	kg	30	60	60	150
Readability	g	5	10	10	20
Platform size	mm	355 x 305	355 x 305	550 x 420	550 x 420
Tower mount height	mm	350	350	700	700
Weight	kg	16.4	16.4	24.5	24.5

Defender 3000 series

As described. Supplied with indicator and tower mount. a.c. adapter and rechargeable battery. A 240V 50/60Hz a.c. single phase supply is required for the adapter.

- BB865-10** Model D31 P30BR
- BB865-20** Model D31 P60BR
- BB865-30** Model D31 P60BL
- BB865-40** Model D31 P150BL

Impact printer, SRP275

With paper rolls, ribbon and mains adapter for 230V 50Hz supplies. Requires printer cable adapter for connection to balances with RS232 output only.

- BB528-12** Printer SRP275
- BD166-48** Paper rolls for BB528-12, pack of 5
- BB528-26** Ink ribbon cassette for BB528-12, pack of 1
- BB605-97** Printer cable adapter for connecting BB865 balances to BB528-12 printer



BB528-12

BB865