

Balances

Precision Electronic Balances, GF- series



- ◆ Super Hybrid Sensor technology gives rapid response and high performance with minimum maintenance
- ◆ Weighing unit modes: g, oz, lb, lb:oz, ozt, ct, mo, dwt, gn, tl, t, msg with %, counting and animal weighing modes
- ◆ Vacuum fluorescent display allows easy reading even with low ambient light, and automatically switches off after 10 minutes without use
- ◆ Automatic adjustable environment setting adapts balance response to the most appropriate for operational conditions
- ◆ One touch calibration using accessory external calibration weight
- ◆ Below balance weighing hook
- ◆ Data memory function holds up to 40 sets of weighing data or 20 sets of unit weight for counting mode
- ◆ Built-in RS232C bi-directional interface
- ◆ Supplied with WinCT software to allow result downloading to the users PC in a Windows™ manageable format

Model		GF-200	GF-300	GF-600	GF-1000	GF-1200	GF-2000	GF-3000	GF-6000
Capacity	g	210	310	610	1100	1210	2100	3100	6100
Readability	g	0.001	0.001	0.001	0.001	0.01	0.01	0.01	0.1
Reproducibility	±g	0.001	0.001	0.001	0.001	0.01	0.01	0.01	0.1
Linearity	±g	0.002	0.002	0.002	0.002	0.02	0.02	0.02	0.1
Pan size	mm	128 x 128 — all models				165 x 165 — all models			
Operating temp.	°C	+5 to +40 at 85% RH or less — all models							
Overall W x D x H	mm	210 x 317 x 138* — all models				210 x 317 x 86 — all models			
Weight	kg	3.8 — all models				4.3 — all models			

*Supplied with a low-profile draught shield.

As described. With WinCT data transfer software, RS232C bi-directional interface, below-balance weighing hook, a.c. adapter for 230V 50/60Hz single phase supplies and instructions.

- BD265-15** Model GF-200
- BD265-25** Model GF-300
- BD265-29** Model GF-600
- BD265-31** Model GF-1000

- BD265-35** Model GF-1200
- BD265-45** Model GF-2000
- BD265-55** Model GF-3000
- BD265-65** Model GF-6000

Accessory

BD255-15 Glass draught shield, OP-10, 220mm high for use with GF200, GF300

External calibration weights - see *BD900/912*.



BD265-25 with BD255-15



BD265-35/BD235-65