

# Centrifuges

## Benchtop Microcentrifuge, uniCFUGE 5

Well-featured, benchtop microcentrifuge providing high performance at a low cost. With lidded rotor accommodating 12 x 1.5/2ml microtubes and adapters for 0.4/0.5ml tubes.

- ◆ Speed range 500 to 15000rpm (maximum rcf: 15595xg)
- ◆ 160 second to 999 minute timer
- ◆ Safety lid interlock
- ◆ Pulse (short spin) function
- ◆ Last run memory feature
- ◆ Large LCD readout of speed, time and process
- ◆ Automatic rotor imbalance switch-off and lid interlock when running
- ◆ USB port and software allows setting/control by the user's computer and storage of up to 99 user-defined programmes

### Microcentrifuge, uniCFUGE 5

As described. Supplied with 12 x 1.5/2ml microtube rotor and lid, adapters for 0.4/0.5ml and 0.2ml tubes, rotor removal Allen key, software CD and manual. Overall 131 x 262 x 230mm H x W x D. Weight 4kg. For 100-240V 50/60Hz single phase supplies.

**CD190-25** uniCFUGE 5

### Accessory rotor for CD190-25

**CD192-04** For 16 x 0.2ml tubes or 2 x strips of 8 x 0.2ml PCR tubes.



CD190-25