

Centrifuges

Student Models

Hand Centrifuge

Reinforced tough polyamide housing with the gear support structure and bench clamp of steel. The gear is self lubricating and runs easily. Maximum speed 3000rpm. Without rotor. PLEASE SEE NOTE BELOW REGARDING THE SUPPLY OF THIS CENTRIFUGE.

CD505-10 Hand centrifuge, without rotor

Accessory Rotors (Load must be balanced), supplied with buckets

CD505-33 For 4 x 15ml (120 x 17mm max.) conical tubes. Max. rcf 1300xg

CD505-36 For 4 x 15ml (127 x 17mm max.) round bottom tubes. Max. rcf 1076xg

SUPPLY OF HAND CENTRIFUGES

We cannot supply these centrifuges for use in the UK. Please check before ordering that the use of this type of centrifuge is permitted in the country where it is to be operated.



CD505-10 with CD505-33

Centrifuge, Clifton Targa

Maximum speed 4000rpm. With enamelled steel outer case and 6 x 15ml (125 x 18mm tube), fixed angle rotor. Maximum rcf 2075xg. With digital controller, allowing display and setting by rpm or rcf and time in minutes and seconds up to 100 minutes. Up to 10 speed and time protocols can be stored in the built-in memory. Also includes safety lid interlock and lid anti-drop mechanism. Overall 296 x 412 x 206mm W x D x H (lid closed). Weight 19kg. For 230V 50/60Hz single phase supplies.

CD545-40 NE010G

Accessories

CD547-04 Adapter, 1 x 3ml (13.5 x 61mm) tube (6 required)

CD547-06 Adapter, 1 x 4ml (13.5 x 65mm) tube (6 required)

CD547-04 Adapter, 1 x 5ml (13.5 x 85mm) tube (6 required)

Gerber centrifuges – see DA450/DA460.

Mikro 200



A low-cost, compact, micro-centrifuge.

- ◆ Maximum speed 15000rpm
- ◆ 0 to 99 minute 59 seconds timer
- ◆ Pulse control
- ◆ 4 programme memory storage

Mikro 200

As described. Maximum speed 15000rpm, with digital control, 0 to 99 minute 59 seconds timer and pulse key. Overall 260 x 275 x 344mm H x W x D. Weight 12kg. For 230V 50/60Hz single phase supplies. Without rotor, adapters or tubes.

CD590-14 Mikro 200

Accessory Angle Rotors

Supplied singly.

CD593-16 24 x 1.5/2ml Max. rpm/rcf 15000/21382xg

CD593-18 30 x 1.5/2ml Max. rpm/rcf 15000/20627xg

Accessory Adapters

Supplied singly.

CD594-05 1 x 0.2/0.4ml (6 x 45mm o.d. x L, max.)

CD594-07 1 x 0.5/0.8ml (8 x 45mm o.d. x L, max.)

CD594-09 1 x 1.5ml* (11 x 38mm o.d. x L, max.)

*Recommended when centrifuging 1.5ml tubes at high speeds.



CD545-40



CD590-14