

# Chromatography

## TLC Separating Chambers

- ◆ Heavy, moulded glass construction
- ◆ Ground flange top and lid for tight seal

### Standard Separating Chamber

For TLC plates 20 x 20cm. With broad grooved flange edge and lid.

**CK610-12** Standard TLC Chamber

### Batch Separating Chamber

With vertical moulded grooves to accommodate up to 5 TLC plates 20 x 20cm. With broad grooved flange edge and lid.

**CK610-22** Batch TLC Chamber

### HPTLC Separating Chamber

For HPTLC and TLC plates 10 x 10cm. With broad grooved flange edge and lid.

**CK610-32** HPTLC Chamber



**CK610-12, CK610-32 is similar**



**CK610-22**

## Chromatography Columns

### Columns

With sintered disc porosity 0 and GP Rotaflo stopcock.

	Dia. mm	Effective length mm	Socket size	GP Rotaflo stopcock bore, mm
<b>QCR10/10</b>	10	100	14/23	3
<b>QCR10/20</b>	10	200	14/23	3
<b>QCR10/30</b>	10	300	14/23	3
<b>QCR10/40</b>	10	400	14/23	3
<b>QCR20/20</b>	20	200	19/26	3
<b>QCR20/30</b>	20	300	19/26	3
<b>QCR20/40</b>	20	400	19/26	3
<b>QCR20/50</b>	20	500	19/26	3
<b>QCR30/40</b>	25	400	24/29	3
<b>QCR30/50</b>	25	500	24/29	3
<b>QCR40/40</b>	30	400	29/32	6
<b>QCR60/40</b>	40	400	40/38	6
<b>QCR60/50</b>	40	500	40/38	6



**QCR10-60:**