

Dissolved Oxygen

Models Oxi3205 and Oxi3310



Portable, precise, rugged, dissolved oxygen meters for field or laboratory use.

- ◆ High resolution, backlit graphics display
- ◆ Autoread function with end-point recognition
- ◆ Automatic atmospheric pressure compensation and salinity compensation
- ◆ Automatic temperature compensation from 0 to 50°C
- ◆ Data storage facility for batch measurement (Oxi3310 only)
- ◆ USB interface
- ◆ Robust, IP67 class housing

Catalogue No.	DT295-25	DT295-35
Model, Oxi-	3205	3310
Ranges	0.00 to 20.00 x 0.01, 0 to 90 x 1 — both models	
x resolution	0.0 to 200.0 x 0.1, 0 to 600 x 1 — both models	
	hPa 0.0 to 200.0 x 0.1, 0 to 1250 x 1 — both models	
temperature, °C	-5.0 to +50.0 x 0.1 — both models	
Accuracy	mg/l O ₂ ±0.5% of value — both models	
	%O ₂ ±0.5% of value — both models	
	hPa ±0.5% of value — both models	
temperature, °C	±0.5% of value — both models	
Calibration	OxiCal [®] rapid calibration — both models (probe dependent)	
Datalogging memories	—	500 — manual 5000 — automatic
Power	4 x 1.5V, AA batteries — both models	
Dimensions	mm 180 x 80 x 55 — both models	
Weight	g 400 — both models	

DO₂ meters, Oxi3205 and Oxi3310, WTW

As described. Supplied with CelloX[®] 325 dissolved oxygen probe, cleaning solution, electrolyte, stand, sample beaker, carrying case, instructions and batteries.

DT295-25 Oxi3205

DT295-35 Oxi3310

Accessories and Spares

DT297-12 Spare DO₂ probe, CelloX[®] 325 with 1.5m cable*

DT297-15 OxiCal[®] SL storage/calibration container for DT297-12

DT297-17 SMPPro rubber protection boot for DT295-series

DT297-19 BOD bottle adapter set for DT295-series

BL610-15 1.5V AA battery (4 required)

* Other cable lengths up to 20m are available - details on request.



DT295-25



DT295-35