

Draining and Drying

Draining Racks

Draining Rack, Azlon

Wall mounting. Epoxy coated steel with 8 pegs 110mm long and 24 pegs 80mm long for holding flasks, cylinders, etc. Overall 410 x 300mm.

DY110-10 Rack only

DY110-27 Rack with integral free standing support

Draining Racks, Bürkle

Wall mounting. Rigid PVC backboard drilled with holes to take interchangeable clip-in pegs in a variety of lengths as indicated. Available in a choice of sizes with, or without, draining trough with nozzle for attaching 4mm i.d.tubing. Supplied with pegs, screws and dowels for fitting.

	Rack W x H, mm	Pegs supplied		
		60mm	100mm	150mm
With draining trough				
DY116-40	400 x 400	5	26	2
DY116-50	500 x 500	10	39	4
DY116-60	600 x 600	15	56	6
Without draining trough				
DY119-40	400 x 400	5	26	2
DY119-50	500 x 500	10	39	4
DY119-60	600 x 600	15	56	6

Spare pegs are available separately – details on request.

Dryer, Drying Cabinets

Dryer, Nelldorn

Bench, or wall mounting. For drying flasks, cylinders etc. Compact metal frame with base mounted heater and fan which blows hot, filtered air through 60 stepped plastic nozzles of varying length. With heat controls, 120 minute timer and overheat cut-out. Overall including tubes 490 x 190 x 430mm W x D x H. For 220-240V 50Hz single phase supplies; 2.1kW.

DY150-20 Nelldorn Dryer

Drying Cabinets

For general warming and drying purposes, including drying of drained glassware. OV100-11 and OV100-21 are additionally fitted with fibre insulation which reduces energy requirements giving a performance saving of more than 30% against the non insulated models.

◆ Maximum temperature is approximately ambient +50°C

OV100-11 100 litres, sliding door, insulated

OV100-14 125 litres, sliding door

Catalogue No.		OV100-11	OV100-14	OV100-21	OV100-25
Capacity	litres	100	125	200	250
Internal	H, mm	400	430	490	520
	W, mm	670	720	930	980
	D, mm	370	400	450	480
Overall	H, mm	600	600	660	660
	W, mm	750	740	1000	1000
	D, mm	420	420	500	500
Weight		45	40	60	55
Shelves		3	3	3	3
Power rating	W	500	1000	1000	1000
Voltage		For 220-240V 50Hz single phase supplies.			

OV100-21 200 litres, sliding door, insulated

OV100-25 250 litres, sliding door

Glassware Washing

Automatic washers – see *Washing* section.

Detergents etc – see *Cleaning and Brushes* sections.

Ultrasonic baths – see *Ultrasonics* section.



DY110 in use



DY116 in use



DY150 in use



OV100