

Extraction

Soxhlet Extractors

Compact extraction systems comprising stand, heating module with variable controller and aluminium block, glassware and cooling manifold (multi-operation units only) for use with mains water or open cooling circulator circuit.

- ◆ Convenient stopcock on the soxhlet body allows solvent to be drained into a storage reservoir after the extraction is complete
- ◆ Rigid metal stand holds glassware securely and is powder-coated to resist corrosion
- ◆ Cooling manifold ensures even distribution of cooling liquid to all condensers

Single extractors

Model	MXT30S	MXT100S	MXT250S
Extractors x capacity ml	1 x 30	1 x 100	1 x 250
Overall, W x D x H mm	230 x 330 x 715	230 x 330 x 805	230 x 330 x 805
Weight, net kg	9	10.5	10.5
Supply requirement	230V 50/60Hz a.c., 450W — all models		

4-place extractors

Model	SXT304ECS	SXT104ECS	SX254ECS
Extractors x capacity ml	4 x 30	4 x 100	4 x 250
Overall, W x D x H mm	530 x 320 x 740	530 x 320 x 740	530 x 320 x 740
Weight, net kg	17	18.5	19
Supply requirement	230V 50/60Hz a.c., 450W — all models		

6-place extractors

Model	SXT306ECS	SXT106ECS	SX256ECS
Extractors x capacity ml	6 x 30	6 x 100	6 x 250
Overall, W x D x H mm	760 x 320 x 720	760 x 320 x 720	760 x 320 x 720
Weight, net kg	20	21	23
Supply requirement	230V 50/60Hz a.c., 450W — all models		

As described. Supplied with stand, heater, and glassware with capacity as indicated. Without extraction thimbles.

EX200-10 MXT30S
EX200-15 MXT100S
EX200-20 MXT250S

EX200-30 SXT304ECS
EX200-35 SXT104ECS
EX200-40 SXT254ECS

EX200-45 SXT306ECS
EX200-50 SXT106ECS
EX200-55 SXT256ECS

Spare Extractors

With solvent drain stopcock.

EX200-85 30ml
EX200-87 100ml
EX200-89 250ml

Soxhlet thimbles

EX100-22 22 x 80mm, for 30ml extractor
EX100-52 33 x 94mm, for 100ml extractor

Soxhlet thimbles for 250ml and extractors - details on request.



EX200-15



EX200-35