

Filtration

Filter Discs

Sintered Discs, Pyrex

Comply with ISO 4793. Discs are flat except 90 and 120mm diameters which are domed for added strength.

	Ref.	Porosity grade	Disc dia. mm		Ref.	Porosity grade	Disc dia. mm
FD300-05	3010/10M	0	10	FD303-05	3010/13M	3	10
FD300-08	3020/10M	0	20	FD303-08	3020/13M	3	20
FD300-12	3030/10M	0	30	FD303-12	3030/13M	3	30
FD300-15	3040/10M	0	40	FD303-15	3040/13M	3	40
FD300-19	3050/10M	0	50	FD303-19	3050/13M	3	50
FD300-26	3090/10M	0	90	FD303-22	3065/13M	3	65
FD301-05	3010/11M	1	10	FD303-26	3090/13M	3	90
FD301-08	3020/11M	1	20	FD303-30	3120/13M	3	120
FD301-12	3030/11M	1	30	FD304-05	3010/14M	4	10
FD301-15	3040/11M	1	40	FD304-08	3020/14M	4	20
FD301-19	3050/11M	1	50	FD304-12	3030/14M	4	30
FD301-22	3065/11M	1	65	FD304-15	3040/14M	4	40
FD301-26	3090/11M	1	90	FD304-22	3065/14M	4	65
FD301-30	3120/11M	1	120	FD304-26	3090/14M	4	90
FD302-05	3010/12M	2	10	FD304-30	3120/14M	4	120
FD302-08	3020/12M	2	20				
FD302-12	3030/12M	2	30				
FD302-15	3040/12M	2	40				
FD302-19	3050/12M	2	50				
FD302-22	3065/12M	2	65				
FD302-26	3090/12M	2	90				
FD302-30	3120/12M	2	120				

Porosity Gradings for Sintered Glassware

Grade	ISO4793 Designation	Pore size index μm
0	P250	160 to 250
1	P160	100 to 160
2	P100	40 to 100
3	P40	16 to 40
4	P16	10 to 16
5	P10	4 to 10



FD300 to FD304