

Furniture

Taps, XL Series

Brownall Labtap®

Robust brass construction finished in "Tektocote" electrostatic epoxy paint and with colour coded controls.

Gas cocks Spring loaded taper plug cocks with drop lever controls.

Water taps Designed and manufactured to Water Research Centre requirements. Suitable for use with hot or cold water.

Needle valve For metering applications and fitted with metering plug. For use with compressed air.

Colour code to DIN 12920:1995-10

Carbon dioxide – Blue with blue/black insert.

Cold water – Green with yellow/blue insert.

Compressed air – Blue with blue/yellow insert.

Hot water – Green with yellow/red insert.

Nitrogen – Blue with green insert.

Oxygen – Blue with blue insert.

Gas

Gas Cock, single

For natural (methane) gas. BSP male thread for horizontal mounting. Light grey.

Drop lever

FZ600-55 BSP 1/4in

Gas Cocks

For natural (methane) gas. BSP 1/4in male thread for vertical mounting flush to the bench top. Outlets on 2- and 4-way versions are 90° apart. With drop levers. Light grey.

FZ603-05 1-way

FZ603-10 2-way

FZ603-15 4-way

Gas burner tubing – see TY280.

Bunsen burners – see BY100/BY250.

Water

Water Taps, swan neck

BSP 1/2 in male thread inlet for vertical mounting flush to a benchtop. Grey with control wheel colour coded for non-potable*, cold water (The mixer taps have two inlets and one hot/one cold control wheel). Choice of fixed or moveable swan neck as indicated (except FZ615-75 which has a removable, aerator nozzle head).

Single swan neck

FZ615-10 Fixed

FZ615-12 Fixed, back-flow resistant**

FZ615-15 Moveable

3-Way (swan neck plus 2 bibs)

FZ615-45 Moveable

Mixer (swan neck plus two controls colour coded one hot/one cold)

FZ615-75 Moveable

* Potable water versions are available - details on request.

** Incorporates a pipe interruptor with air gap at the nozzle and 300mm clearance from nozzle to bench/sink top in compliance with UK water regulation AUK3.

Compressed Gas

Needle Valves, compressed gas

BSP 1/2 in male thread inlet for horizontal mounting. With single outlet. Light grey with hand wheel colour coded for gases as indicated.

Note: All gases must be dry.

FZ645-10 1-way, compressed air

FZ645-13 1-way, nitrogen

FZ645-16 1-way, oxygen

FZ645-19 1-way, carbon dioxide



FZ600-55



FZ603-05



FZ615-75



FZ615-10, FZ615-12 and FZ615-15 are similar



FZ615-45



FZ645-13