

# Heating

## Kjeldahl Heater Units, EH-200-series

**Cole-Parmer®**

an antylia scientific company

### Macro Digestion/Distillation Units, Cole-Parmer

With choice of two or six recesses and flask capacities as table. Recesses are at 150mm centres. Aluminium case with energy regulators and brackets to accept 12.5mm diameter support rods or the flask rest supplied. The 6-recess models have also clamps at either end of the case to accept 15.8mm diameter support rods. Maximum heater element temperature 800°C. For 230V a.c. single phase supplies. Formerly MQ38xx-series.

	Ref. EH-	Recesses	Flask capacity ml	Total rating W	Dimensions W x D mm
<b>KJ300-12</b>	200-2	2	100 to 300	600	305 x 203
<b>KJ300-16</b>	200-2-L	2	500 to 800	1100	305 x 203
<b>KJ305-16</b>	200-6-L	6	500 to 800	3300	914 x 203

Spare heaters for KJ300-series - details on request.

## Hot Air Blower

### Hot Air Blower (Heat Gun), heavy duty

Suitable for a wide range of uses where localised rapid heating is required.

- ◆ Drying chromatography papers
- ◆ Sterilising
- ◆ Drying glassware
- ◆ Concentrating solutions

Ruggedly constructed, with rugged, industrial plastic housing and satin chrome nozzle and end baffle. A ceramic heating element ensures a long operational life. Can be hand-held or self-standing in an upright position. Includes safety thermostat and thermal fuse. Three heat/airflow settings are available: 50°C/200 litres per minute, 400°C/300 litres per minute and 600°C/500 litres per minute. Heater rating 1800W. Overall 260 x 90 x 205mm H x W x D. Weight 780g. For 230V 50Hz single phase supplies.

**HE775-60** HL1820S

Impulse heat sealer for plastic film and laminates – see TS400.



**KJ300**



**HE775-60**



**KJ305**