

Incubators

Cooled Incubators

Lovibond®

- ◆ Temperature range: +2 to +40°C x 0.1°C
- ◆ Temperature fluctuation ±1°C (stirred 500ml water at centre of cabinet).
For BOD (T = 20°C) ±0.5°C
- ◆ R134a refrigerant
- ◆ Backlit LED temperature display
- ◆ Fan-assisted cooling
- ◆ Choice of glass-panelled or solid door models
- ◆ Built-in internal sockets (Europlug, Schuko-type) for operating instruments inside the cabinet

Model	Solid door, TC- Glass door, TC-	135S	— 140G	710S 715G	720S —
Capacity	litres	135	140	288	488
Internal (external)	H	mm	700 (850)	700 (885)	1545 (1684)
	W	mm	430 (600)	443 (600)	415 (600)
	D	mm	515 (600)	515 (600)	515 (654)
Shelves supplied		3	3	3	3
Internal sockets supplied		4	4	5	5
Net weight	kg	39	50	73	74

As described. With digital controller and backlit LED display, solid or glass-paned door and shelves and sockets as indicated. For 230V 50Hz single phase supplies.

Solid door models

IN686-12 TC135S
IN686-28 TC710S
IN686-37 TC720S

Glass door models

IN686-62 TC140G
IN686-71 TC715G



IN686-62 in use with WR245-10

IN686-12 to -37