

Incubators

Cooled Incubators

Lovibond®

- ◆ Temperature range: +2 to +40°C x 0.1°C
- ◆ Temperature fluctuation ±1°C (stirred 500ml water at centre of cabinet).
For BOD (T = 20°C) ±0.5°C
- ◆ R134a refrigerant
- ◆ Backlit LED temperature display
- ◆ Fan-assisted cooling
- ◆ Choice of glass-panelled or solid door models
- ◆ Built-in internal sockets (Europlug, Schuko-type) for operating instruments inside the cabinet

Model	Solid door, TC- Glass door, TC-	135S	— 140G	175S	255S	— 256G	445S
Capacity	litres	135	140	175	255	255	445
Internal (external)	H	mm	700 (850)	700 (885)	1045 (1216)	1450 (1590)	1300 (1516)
	W	mm	430 (600)	443 (600)	415 (600)	415 (600)	515 (710)
	D	mm	515 (600)	515 (600)	515 (600)	515 (600)	652 (752)
Shelves supplied		3	3	3	4	4	5
Internal sockets supplied		4	4	5	7	7	9
Net weight	kg	39	50	49	64.5	82	79.5

As described. With digital controller and backlit LED display, solid or glass-paned door and shelves and sockets as indicated. For 230V 50Hz single phase supplies.

Solid door models

IN686-12 TC135S
IN686-22 TC175S
IN686-32 TC255S
IN686-42 TC445S

Glass door models

IN686-62 TC140G
IN686-82 TC256G



IN686-62 to -82 in use with WR245-10

IN686-12 to -42