

Ovens

Drying Cabinets



Drying Cabinets

For general warming and drying purposes, including drying of drained glassware. OV100-11, OV100-21, OV105-12 and OV105-17 are additionally fitted with fibre insulation which reduces energy requirements giving a performance saving of more than 30% against the non insulated models.

- ◆ Maximum temperature is approximately ambient +50°C
- ◆ Choice of:
 - Sliding toughened glass door with or without insulation
 - Hinged toughened glass door (2 on 885 litre and 1000 litre models) with or without insulation
- ◆ Stoved enamel paint interior and exterior
- ◆ Chromium plated wire mesh shelves
- ◆ Simmerstat heat control
- ◆ Hinged door models have fan circulation

Sliding door models

Catalogue No.		OV100-11	OV100-14	OV100-21	OV100-25
Capacity	litres	100	125	200	250
Internal	H, mm	400	430	490	520
	W, mm	670	720	930	980
	D, mm	370	400	450	480
Overall	H, mm	600	600	660	660
	W, mm	750	740	1000	1000
	D, mm	420	420	500	500
Weight		45	40	60	55
Shelves		3	3	3	3
Power rating	W	500	1000	1000	1000
Voltage		For 220-240V 50Hz single phase supplies.			

- OV100-11** 100 litres, sliding door, insulated
- OV100-14** 125 litres, sliding door
- OV100-21** 200 litres, sliding door, insulated
- OV100-25** 250 litres, sliding door

Hinged door models

Catalogue No.		OV105-09	OV105-12	OV105-16	OV105-17
Capacity	litres	425	500	885	1000
Internal	H, mm	1350	1380	1350	1380
	W, mm	530	580	1110	1160
	D, mm	590	620	590	620
Overall	H, mm	1680	1680	1680	1680
	W, mm	600	600	1180	1180
	D, mm	600	650	650	650
Weight	kg	80	75	140	130
Shelves		3, adjustable for height — all models			
Power rating	W	1000	1000	1750	1750
Voltage		For 220-240V 50Hz single phase supplies			

- OV105-09** 425 litres, hinged door, insulated
- OV105-12** 500 litres, hinged door
- OV105-16** 885 litres, hinged door, insulated
- OV105-17** 1000 litres, hinged door

Glassware Dryer

For drying flasks, cylinders by hot air blowing – see *DY150* in the *Drying* section.



OV100



OV105