

Ovens

Mino Range 250°C



- ◆ Standard profile with controls at base
- ◆ Temperature range 40 to 250°C
- ◆ Fluctuation $\pm 0.75^\circ\text{C}$
- ◆ Choice of:
 - Aluminium coated mild steel or stainless steel interiors
 - Natural or fan convection (30 litre models and above)
- ◆ Hydraulic thermostat with locking device
- ◆ Adjustable safety thermostat with indicator lamp and locking device
- ◆ Top vent with clip for thermometer
- ◆ Fan mounted at rear
- ◆ Fitted with fixed shelf runners and removable chrome-plated wire grid shelves
- ◆ Steel outer case with stoved powder paint finish

MINO range, standard profile

Catalogue No.	OV160 OV164	-05 —	-07 —	-20 -20	-22 -22	-30 -30	-32 -32	-40 -40	-42 -42
Usable volume	litres	6	18	30	30	50	50	75	75
External	H	mm	390	520	500	500	580	580	590
	W	mm	320	380	480	480	610	610	610
	D*	mm	330	410	490	490	470	470	600
Internal	H	mm	150	260	240	240	330	330	330
	W	mm	230	260	360	360	490	490	490
	D	mm	190	270	350	350	330	330	450
Power rating	W	300	500	750	750	1000	1000	1250	1250
Shelves supplied		1	2	2	2	2	2	2	2
Shelf positions		1	2	2	2	3	3	3	3
Weight	kg	7	14	20	20	26	26	34	34

*Fan convection models have external depth increased by 120mm.

Ovens, standard profile, MINO 250°C

As described. With aluminium coated steel (CLAD) or stainless steel interior as indicated, shelves, control and safety thermostats, mains on/off switch and indicator lamps. For 220-240V 50Hz single phase supplies.

Natural convection

- OV160-05 6 litres, CLAD
- OV160-07 18 litres, CLAD
- OV160-20 30 litres, CLAD
- OV160-22 30 litres, stainless steel
- OV160-30 50 litres, CLAD
- OV160-32 50 litres, stainless steel
- OV160-40 75 litres, CLAD
- OV160-42 75 litres, stainless steel

Fan convection

- OV164-20 30 litres, CLAD
- OV164-22 30 litres, stainless steel
- OV164-30 50 litres, CLAD
- OV164-32 50 litres, stainless steel
- OV164-40 75 litres, CLAD
- OV164-42 75 litres, stainless steel



OV160/OV164