

pH Meters

Hand-held pH Testers 206-Series



Convenient, hand-held meters with innovative, replaceable probe system which resists clogging by replacement of the conventional microporous membrane with a hole diaphragm and solid gel electrolyte. Low membrane resistance also results in fast, accurate readings.

- ◆ Choice of models:
 - 206-pH1 for liquids
 - 206-pH2 for semi-solids
- ◆ Generous electrolyte volume provides extended life
- ◆ Maintenance-free
- ◆ Almost unbreakable probe design
- ◆ 1, 2 or 3-point calibration
- ◆ Leakproof, KCL gel-filled, probe storage cap
- ◆ Dual display (pH and °C)
- ◆ Built-in temperature probe
- ◆ Includes IP68 "TopSafe" protection case

Specification for both models

Range	pH	0 to 14.00
	°C	0 to 60
Resolution	pH	0.01
	°C	0.1
Accuracy	pH	±0.02
	°C	±0.4
Temp. comp.	°C	Automatic over full range
Auto calibration		1 to 3 point (pH4.0, pH7.00 and pH10.1 recognised)
Display		Twin-line LCD, simultaneous pH and °C readout
Power		1 x 3V CR2032 battery
Overall L x W x D	mm	197 x 33 x 20
Weight	g	69

As described. Supplied with probe module, "TopSafe" protection case, storage cap with KCL gel storage medium, belt clip/wall-mounting holster and battery.

- PJ335-10** Testo 206-pH1
- PJ335-20** Testo 206-pH2

Accessories and Spares

- PJ337-04** Spare probe for PJ335-10 only with gel storage cap
- PJ337-08** Spare probe for PJ335-20 only with gel storage cap
- BL590-25** Spare battery, 3V



PJ335

Food Testing pH Meter



- ◆ Ergonomic design for ease of use
- ◆ Penetration probe with built-in combination electrode and temperature probe, in an almost unbreakable housing
- ◆ Maintenance-free, gel electrolyte
- ◆ Back-lit, dual LCD readout of all pH and temperature
- ◆ Automatic reading stability detection
- ◆ 1, 2 or 3-point calibration
- ◆ Leakproof, KCL gel-filled, probe storage cap
- ◆ IP65 housing

Specification

Range	pH	0 to 14.00
	°C	0 to 60
Resolution	pH	0.01
	°C	0.1
Accuracy	pH	±0.02
	°C	±0.4
Temp. comp.	°C	Automatic over full range
Auto calibration		1 to 3 point (pH4.0, pH7.00 and pH10.1 recognised)
Display		Twin-line LCD, simultaneous pH and °C readout
Power		4 x 1.4V LR44 batteries
Overall L x W x D mm		197 x 33 x 168
Weight	g	69

As described. Supplied with probe module, storage cap with KCL gel storage medium, wall-mounting holder and batteries.

- PJ342-15** Testo 205

Accessories and Spares

- PJ342-40** Spare probe for PJ342-15 with gel storage cap
- PJ342-45** Spare gel storage cap
- BL610-04** 1.4V battery (4 required)



PJ342-15