

pH Meters

Portable pH meters 550 and 570



- ◆ Choice of models:
 - Model 550: simultaneous pH/temperature LCD readout with splashproof (IP65-rated) housing
 - Model 570: simultaneous pH or mV and temperature LCD readout with battery indicator and waterproof (IP66-minimum rated) housing
- ◆ Manual or automatic temperature compensation
- ◆ Automatic, two-point pH calibration with automatic buffer recognition
- ◆ Auto shut-off after 10 minutes of inactivity to conserve battery life

Catalogue No.		PJ360-40	PJ360-70
Model		550	570
Ranges (resolution)	pH	0 to 14.00 x 0.01	-2.00 to 16.00 x 0.01
	mV	-	-1000 to +1000 x 1
	°C	0 to 100.0 x 0.1	-39.9 to 149.9 x 0.1
Accuracy	pH	±0.05	±0.02
	mV	-	±1
	°C	±0.5	±0.4 (between -10 and +70°C)
ATC range		0 to 60°C	0 to 100°C
Calibration		2 point on standard solutions with automatic buffer recognition	
Inputs		BNC and 3.5mm jack	BNC/Lumberg screwlock
Power		3 x 1.5V AAA batteries – both models	
Dimensions L x W x D	mm	141 x 56 x 25	141 x 71 x 32
Weight	kg	0.13	0.23

Portable pH meters 550, 570, Jenway

As described. Supplied with epoxy-bodied, gel-filled pH electrode, ATC probe, 3 x 1.5V batteries, 1 each pH4, pH7 and pH10 buffer sachets, carrying case and instructions.

PJ360-40 Model 550 with case

PJ360-70 Model 570 with case

Spares and Accessories

PJ364-08 Spare combination pH electrode, epoxy bodied, gel filled

PJ364-15 Spare temperature/ATC probe for PJ360-40 only

PJ364-17 Spare temperature/ATC probe for PJ360-70 only

BL610-08 Spare battery, 1.5V (3 required)



PJ360-40



PJ360-70



+44 (0)20 7729 2405

e-mail: export@ajcope.co.uk fax orders: +44 (0)20 7729 2657

