Pipette Controller, accu-jet S

- ◆ Ergonomic, lightweight design for fatigue-free use
- ◆ Suitable for pipettes from 0.1 to 100ml
- ◆ Continuously adjustable power with simple, two-button, fingertip control offering gravity (for delivery-calibrated pipettes) or powered blow-out delivery (for pipettes calibrated to contain)
- ◆ Cordless operation with rechargeable NiCd battery
- ◆ Rapid battery recharging
- ◆ The controller can be stood on its end whilst on the bench with a pipette in place
- ◆ Pipetted media fumes vented at front of pipettor reducing the possibility of internal corrosion
- ◆ Supplied with universal charger for U.K.. Europe, USA, Japan, Australia and New Zealand configurations

As described. With fully autoclavable pipette connector, disposable 0.2μm membrane filter and one way safety valve. Supplied with wall support, two spare 0.2μm membrane filters and universal charger for the rechargeable battery. Weight 205g.

PP895-70 accu-jet S with universal charger for 100-240V 50/60Hz single phase supplies

Accessories and Spares for PP895 series

PP897-09 0.2μm membrane filter. sterile, supplied singly
PP897-10 0.2μm membrane filter. non-sterile, pack of 10
PP897-16 3μm membrane filter. non-sterile, pack of 10
PP897-34 Spare universal charger for 100-240V 50/60Hz single phase supplies
PP897-54 Wall support

Pipette Boxes

For holding pipettes for autoclaving or dry heat sterilising up to 180°C. With lid.

Cylindrical pattern

	Length x dia. mm	Material
PP970-30	407 x 64	Aluminium
PP970-50	457 x 64	Aluminium
PP970-55	457 x 64	Stainless steel

Square section pattern
The lid and base have a built-in silicone pad. The square section is 70 x 70mm.

	Length, mm Int. x Ext.	Material
PP975-14	175 x 210	Stainless steel
PP975-18	250 x 290	Stainless steel
PP975-22	300 x 340	Stainless steel
PP975-27	390 x 430	Stainless steel
PP975-32	450 x 490	Stainless steel

Pipette rinser – *see WB610.*

Pipette stands – *see SM200/SM254.*

PP895-70

PP970-30 to -55, PP975 plus Petri dish holder