

# Pumps, air/gas/vacuum

## Portable Vacuum Pump/Compressor, LLG uniVACUUPUMP 1

Simple, compact, portable, oil-free, piston pump housed in a lightweight plastic casing with handle for general duty applications requiring only a rough vacuum and moderate pressure. Ideal water jet or aspirator replacement. Not suitable for use with organic, basic or acidic vapours and gases. Free air displacement 9.2 litres/minute, ultimate vacuum 292mbar. Overall 191 x 194 x 114mm H x W x D. Weight 2.3kg. Supplied with 1.8 metre power supply cable. For 230V 50Hz single phase supplies.

**PX240-20** Model uniVACUUPUMP 1

## Dry Piston Pumps, WOB-L®



Oil-free, vacuum/pressure piston pumps ideal for air sampling, pressure or vacuum filtration, water aeration or for use with vacuum ovens or flame photometers. Not suitable for use with organic, basic or acidic vapours and gases.

- ◆ Built for continuous-duty operation
- ◆ All parts in contact with air are aluminium or stainless steel and corrosion-protected from moisture
- ◆ All pumps supplied with thermally protected motor, carrying handle and suction cup feet for stability

Catalogue No.	PX245-15	PX245-20	PX245-59
Model No.	2522C-02	2534C-02	2546C-02
Stages	1	1	1
Free air displacement litres/minute	18	28	38
Ultimate vacuum mbar	133	93	80
Pressure bar	1	0.5	1
Hose connections, i.d. mm	5	5	5
Overall H mm	254	254	254
W mm	224	224	191
D mm	206	206	229
Weight kg	5.3	5.3	6.3

As described. Supplied with mains lead. For 230V 50Hz single phase supplies.

**PX245-15** Model 2522C-02, complete with vacuum and pressure gauges, regulators, silencer and water trap

**PX245-20** Model 2534C-02, complete with vacuum and pressure gauges, regulators, silencer and water trap

**PX245-59** Model 2546C-02, complete with vacuum and pressure gauges, regulators, silencer and water trap



PX240



PX245-15I-20, PX245-59 is similar