Diaphragm Liquid Pumps, LIQUIPORT®

Convenient, simple transfer or dosing pumps for corrosive or non-corrosive liquids.

- Self-priming and able to run dry
- PTFE-coated diaphragm and FFPM valves, with choice of pumphead material in contact with med - polypropylene, PVDF or PTFE
- Low maintenance design
- Continuously adjustable flow rate with dial control with LED indicators which illuminate sequentially as the rate is increased

Model		NF100**18S	NF1.100**18S	NF300**18S	NF1.300**18S
Flow rate	*ml/min**	0.2 to 1.3	0.2 to 1.3	0.5 to 3.0	0.5 to 3.0
Pressure head	*mWg*	10	60	10	60
Suction head	*mWg*	3	3	3	3
Housing protection level		IP65	IP65	IP65	IP65
Hose connection	*o.d. mm*	8	8	12	12
Overall	*H x W x D mm*	180 x 100 x 130	180 x 100 x 130	190 x 110 x 160	190 x 110 x 160
Weight	*kg*	1	1	1.5	1.5

*Using water at 20°C and zero pressure head
**Pump head material code key: KT. = polypropylene TT. = PVDF FT. = PTFE

Diaphragm Liquid Pumps, LIQUIPORT®
As described. For 100-230V, 50/60Hz single phase supplies. In pumphead material as indicated.

PX587-06	NF100KT.18S	***PX589-07***	NF300KT.18S
PX587-12	NF100TT.18S	***PX589-13***	NF300TT.18S
PX587-18	NF100FT.18S	***PX589-19***	NF300FT.18S
PX587-24	NF1.100KT.18S	***PX589-25***	NF1.300KT.18S
PX587-30	NF1.100TT.18S	***PX589-31***	NF1.300TT.18S
PX587-36	NF1.100FT.18S	***PX589-36***	NF1.300FT.18S

PX587- and PX589-series