

Ancillary Items for use with Quickfit Glassware

PTFE Sleeves, Azlon disposable

For fitting over ground glass cones to provide greaseless lubrication. Wall thickness 0.07mm, taper 1:10. Supplied in packs of 10.

	Ref.	For cone
QZZ20/14	SWN961	14/23
QZZ20/19	SWN962	19/26
QZZ20/24	SWN963	24/29
QZZ20/29	SWN964	29/32
QZZ20/34	SWN965	34/35
QZZ20/40	SWN966	40/38
QZZ20/55	SWN969	55/44

PTFE Sleeves, reusable

With knurled shoulder for ease of handling. Supplied singly.

	For cone
QZZ25/14	14/23
QZZ25/19	19/26
QZZ25/24	24/29
QZZ25/29	29/32

PTFE Sealing rings, reusable

Fine (0.7mm wide, 0.07mm thick) PTFE sealing rings for ground glass cones. In use the ring is carefully stretched onto the cone, becoming elastic and producing a tighter seal than conventional full sized sleeves (solvent leak rate <0.2mg/day). Operating temperature range -20 to +300°C. Supplied in packs of 50, mounted on an applicator tube.

	Ref.	For cone
QZZ27/14	N14	14/23
QZZ27/19	N19	19/26
QZZ27/24	N24	24/29
QZZ27/29	N29	29/32
QZZ27/34	N34	34/35
QZZ27/45	N45	45/25

Reduction adapters, PTFE, Azlon

Supplied singly.

	Ref.	Socket	Cone
QZZ35-02	SWN902	10/19	14/23
QZZ35-04	SWN904	14/23	19/26
QZZ35-07	SWN907	19/26	29/32
QZZ35-08	SWN908	19/26	34/35
QZZ35-09	SWN909	24/29	29/32
QZZ35-10	SWN910	24/29	34/35
QZZ35-11	SWN911	29/32	34/35



QZZ20 in use



QZZ25



QZZ27 in use