Refrigeration

Pharmacy Refrigerators



Specifically designed for the storage of vaccines, insulin, temperature-sensitive samples and pharmaceuticals. Maintain internal air temperature between +2°C and +8°C.

Choice of controller:

Control (RG230-series) — digital controller monitoring internal air temperature only. Max./min. memory and audio-visual alarm

Control Plus (RG232-series) — digital controller monitoring internal air and load (product) temperatures using additional glycol-immersed probe (-BT-models also incorporate Bluetooth connectivity and smart phone app for data monitoring and temperature control). Additionally have a 16mm porthole allowing further auxiliary probes to access the internal chamber

- Forced air cooling for temperature stability and rapid temperature recovery after door opening
- Audio-visual alarm signal if internal temperature exceeds operating range.

As described. With solid or glass door, door lock, adjustable wire shelves, and wire base basket as indicated. For 230V 50Hz single phase supplies.

	Model	Gross cap. litres	H x W x D, mm	Shelves/ baskets supplied	Internal light
Solid door models					
RG230-13	PESR41UK	41	705 x 380 x 500	2/0	No
RG230-24	PESR82UK	82	660 x 502 x 540	2/1	No
RG230-27	PESR107UK	107	835 x 505 x 620	2/1	No
RG230-58	PE1607C	444	1688 x 685 x 910	5/0	No
RG232-14	PPSR47BTUK	47	565 x 475x 445	2/0	Yes
RG232-31	PPSR158BTUK	158	850 x 595 x 660	3/1	Yes
RG232-47	PPSR310BTUK	310	1500 x 595 x 660	5/1	Yes
RG232-51	PPSR400BTUK	400	1935 x 595 x 660	6/1	Yes
Glass door models					
RG230-62	PEGR41UK	41	705 x 380 x 500	2/0	No
RG230-66	PEGR82UK	82	660 x 502 x 540	2/1	No
RG230-68	PEGR107UK	107	835 x 505 x 620	2/1	No
RG230-94	PG1607C	444	1688 x 685 x 910	5/0	No
RG232-61	PPGR47BTUK	47	565 x 480 x 505	2/0	Yes
RG232-71	PPGR158BTUK	158	850 x 595 x 660	3/1	Yes
RG232-81	PPGR310BTUK	310	1500 x 595 x 660	5/1	Yes
RG232-87	PPGR400BTUK	400	1935 x 595 x 660	6/1	Yes



RG230-24

- Integral door lock with 2 keys and open door alarm (except 41 and 47 litre models)
- Automatic defrost
- Refrigerants:
 - R134a (RG230-models only) R600a (RG232-models only)
- Adjustable shelf levels
- Glass door and built-in illumination models available
- Anti-microbial door handle

Note:

Due to the large size and weight of these units the user must ensure that suitable space area, floor loading and access for installation is available prior to ordering. They are installable by the user and delivery therefore will only be made to the customers unloading area.

R600a refrigerant models cannot be transported by airfreight due to the hazardous nature of this refrigerant. They can therefore only be exported by overland or seafreight.



RG232-70





O207 729 7998
e-mail: customer.services@thelabwarehouse.com fax orders: 020 7729 2657