

Safety

Coveralls

KleenGuard
BRAND

- ◆ Wide range of materials for protection against dusts through to chemical spray or jetted liquids.
- ◆ CE0120 assured to category 3. Complex design

Performance Data

Product	Test method	Class/Result	A25	A40	A50	A80
Fabric Tests						
Abrasion resistance	EN530 method 2		1	6	2	6
Flex cracking resistance	ISO7854 method B		1	4	4	5
Trapezoidal tear resistance	ISO9073-4		1	2	2	3
Puncture resistance	EN863		1	2	1	2
Tensile strength	ENISO13934-1		1	1	1	2
Liquid repellency/penetration resistance	EN368 (10% NaOH)		3/3	3/3	3/3	6/6*
	EN368 (30% H ₂ SO ₄)		2/3	3/3	3/3	6/6*
Ignition resistance	EN13274-4 method 3		pass	pass	pass	pass
Seam strength	EN ISO 13935-2		2	3	3	4
Surface resistivity (inside surface),	EN1149-1:1995		—	—	<5 x 10 ¹⁰	<5 x 10 ¹⁰
Infective agents	EN14126:2003		—	—	—	pass
Garment Tests						
Liquid spray penetration (mist test)	EN468		pass	pass	pass	pass
Aerosol/fine particle penetration	pr ISO13982-2 (average total inward leakage)		4.27%	5.09%	6.4%	3.6%
Radioactive dust†	EN1073-2:2002		—	1	1	1

Tests performed with taping at wrists, ankles and hood.

*Tested under EN374:3 with Class 6 result at all levels.

†Provide no protection against radioactive radiation.

Continued on next page



SA335 in use



SA337 in use

Safety

Coveralls continued

KleenGuard
BRAND

Coveralls, A25

General purpose, liquid and particle protection coverall in breathable white, silicone-free, SMS fabric with grey stretchable film laminate band for additional user comfort. Triple stitched internal seams resist tearing. Supplied in packs of 25.

- SA335-10 Small
- SA335-20 Medium
- SA335-30 Large
- SA335-40 X-Large
- SA335-50 XX-Large

Coveralls, A40

White, ultra-low linting, film laminate material coverall for protection against chemical splashes and particles. Fabric is also antistatic to EN1149-1 and silicone-free. Supplied in packs of 25.

- SA337-10 Small
- SA337-20 Medium
- SA337-30 Large
- SA337-40 X-Large
- SA337-50 XX-Large

Coveralls, A50

White, durable, breathable SMS fabric treated for increased protection against chemical splashes. Low-linting, antistatic and silicone-free. With 2-way zip for quick easy access to work clothes. Supplied in packs of 25.

- SA339-10 Small
- SA339-20 Medium
- SA339-30 Large
- SA339-40 X-Large
- SA339-50 XX-Large

Garment sizing

All garments comply with EN340 recommendations:

Designation	Chest, cm	Height, cm
Small	96-104	164-170
Medium	104-112	170-176
Large	112-120	176-182
X-Large	120-128	182-188
XX-Large	128-136	188-194



SA339 in use