

# Safety

## Flammable Storage Cabinets, Dual Compliance

- ◆ Comply fully with EN14470-1 (30 minute fire resistance - ISO834 test) and FM6050
- ◆ Melamine-faced, wooden construction offers excellent chemical resistance and structural rigidity
- ◆ Self-closing doors and inlet/outlet vents with fused links which shut the doors automatically and seal the ventilation system if the ambient temperature exceeds 43°C
- ◆ 3-point locking of doors ensure high security
- ◆ Base trough provided for easy collection and disposal of spillages
- ◆ Larger cabinets have tray-type, steel shelves for minor spillages, which are height-adjustable
- ◆ Labelled in accordance with ISO3684, EN14470-1 (04/2004), FM6050 and European Directive 92/58/CEE

Catalogue No.	<b>SB858-15*</b>	<b>SB858-25*</b>	<b>SB858-35</b>	<b>SB858-45</b>	<b>SB858-55</b>
Capacity, litres	30	60	130	170	250
U.S. Gallons	8	16	34	45	68
Doors	Single	Double	Single	Double	Double
Shelves	—	—	3	2	3
Base trough, litres	20	41	20	31	41
Overall H mm	700	900	700	900	1800
W mm	350	460	900	900	900
D mm	300	460	460	460	460
Weight, kg	64	108	117	210	225

\* Underbench models

As described. Supplied with adjustable tray shelves as indicated and instructions.

- SB858-15** Dual range flammable storage cabinet, 30 litres
- SB858-25** Dual range flammable storage cabinet, 60 litres
- SB858-35** Dual range flammable storage cabinet, 130 litres
- SB858-45** Dual range flammable storage cabinet, 170 litres
- SB858-55** Dual range flammable storage cabinet, 250 litres

### Accessory additional shelves for SB858-series

Steel, tray-type. For cabinets as indicated.

- SB858-80** For cabinet SB858-35
- SB858-82** For cabinets SB858-45/55



SB858