

Safety

Fire-Resistant Acid and Alkali Storage Cabinet

- ◆ Fire-resistant up to 30 minutes according to ISO834 test conditions
- ◆ Compliant with EN14470-1 (if used with accessory fume extraction system) and EN1363-1
- ◆ Independent compartments for acids and alkali storage
- ◆ Earthing point to dissipate static electricity
- ◆ Intumescent seals for doors and vent
- ◆ Self-closing doors with key lock

Accessories

- SB859-22** Spare/accessory shelf
- SB859-25** Extraction system. Steel construction with fan, activated charcoal filter, connection kit to mount onto cabinet, 1 metre flexible exhaust hose, and 100mm diameter clips/clamps. For 220-240V 50Hz single phase supplies

Catalogue No.	SB859-10	
Capacity	litres	300
Adjustable shelves	6 (3 per compartment), 30kg capacity each	
Base trough	2 (1 per compartment)	
Doors	2	
Mounting	Pedestal with removable front panel for manoeuvre by forklift	
Overall (internal)	H mm	1900 (1545)
	W mm	1120 (1015)
	D mm	550 (440)
Weight	kg	230

Note:

Due to the large size and weight of this unit the user must ensure that suitable space area, floor loading and access for installation is available prior to ordering. It is installable by the user and delivery therefore will only be made to the customers unloading area.

It is the responsibility of the user to ensure adequate extraction or venting is available for connection of the extraction exhaust hose.

As described. Supplied with shelves and base trough as indicated.

SB859-10 Fire resistant acid and alkali storage cabinet



SB859-10 in use