

# Stirrers, Overhead

## Overhead Stirrers

### Stirrer, IKA Eurostar 40 digital

An economically priced stirrer suitable for up to 25 litres of low to medium viscosity liquids up to 30000 mPas. Continuously variable, microprocessor controlled speed range 30 to 2000rpm with LED digital speed display. With 0.5 to 10mm i.d. hollow shafted chuck and 16mm diameter clamping rod for mounting on a stand. Overall W x D x H 86 x 208 x 248mm. Weight 4.4kg. For 230V 50/60Hz single phase supplies. Without rotor.

**SR730-35** Eurostar 40 digital

### Stirrer, IKA Eurostar 60 Control

Powerful digital stirrer suitable for up to 40 litres of medium to high viscosity liquids up to 50000 mPas. Removable, multifunctional controller, with wireless connection, TFT display and continuously variable, microprocessor controlled speed range 30 to 2000rpm. Includes display of set/actual speed and temperature (-10 to +350°C, using accessory probe) with safety cut-out, torque and timer function, and USB and RS232 interfaces. With 0.5 to 10mm i.d. hollow shafted chuck and 16mm diameter clamping rod for mounting on a stand. Overall W x D x H 86 x 230 x 267mm. Weight 4.7kg. For 230V 50/60Hz single phase supplies. Without rotor.

**SR730-50** Eurostar 60 control

### Stirrer, IKA RW20 digital

A robust stirrer for processing up to 20 litres of medium viscosity liquids up to 10000 mPas. With digital speed display, adjustable two-speed ranges: 60 to 500 and 240 to 2000rpm, and 1 to 10mm i.d., hollow shafted chuck. Also incorporates an electronic temperature safety cut-out on the motor and 13mm diameter clamping rod for mounting on a stand. Overall dimensions 88 x 212 x 294mm W x D x H. Weight 3.1kg. For 230V 50/60Hz single phase supplies. Without rotor.

**SR750-25** RW20 digital

### Accessories for Eurostar and RW20 stirrers

#### Stand

Base Plate 200 x 316mm and 16mm diameter stainless steel rod, 800mm high. Maximum loading capacity 5kg.

**MT468-22** Stand R1826

#### Bosshead R182

For clamping Eurostar and RW20 stirrer rods to stands. With quick release screws. Accepts rod diameters from 6 to 16mm.

**SR753-09** Bosshead R182

### Accessory temperature probes for Eurostar 60 Control model only

**SR753-80** H 62.51 stainless steel temperature probe

**SR753-85** H 66.51 stainless steel, glass coated, temperature probe

### Stirrer, IKA RW28 digital

A heavy duty stirrer for processing up to 80 litres of medium viscosity liquids. With two reversible speed ranges 60 to 400 and 240 to 1400rpm. Provides high torque at the lower speeds. With high resolution, 4-digit, LED display, 1 to 10mm chuck and an infinitely variable mechanical speed control. Overall W x D x H 123 x 252 x 364mm. Weight 7.4kg. For 230V 50/60Hz single phase supplies. Without rotor.

**SR765-25** RW28 digital

### Accessories for RW28 digital stirrer

#### Heavy duty H-stand 2722

With stainless steel rod, 1010mm high.

**MT492-08** Stand 2722

#### Bosshead R271

For clamping stirrer rod to stand.

**SR768-14** Bosshead R271

### Rotors, stainless steel

Suitable for all models. On 8mm diameter shaft.

	Ref.	Impellor length	Shaft
<b>SR753-14</b>	R1375	Blade 70 x 70mm	550mm
<b>SR753-17</b>	R1345	Propellor 4-blade 100mm dia.	550mm
<b>SR753-19</b>	R1300	Dissolving 80mm dia.	350mm
<b>SR753-23</b>	R1312	Turbine 50mm dia.	350mm



SR730-50, SR730-35 is similar



SR753-09



SR750-25 with accessories



SR765-25