

Tiles

Tiles

Cavity Tile/Plate, plastic

White polypropylene. With 12 cavities. Suitable for spotting applications. 115 x 95mm. Supplied singly.

TJ995-10 Cavity tile, plastic

Cavity Tile/Plate, ceramic

White glazed ceramic with 12 cavities. Suitable for spotting applications. 115 x 90mm. Supplied singly.

TJ995-25 Cavity tile, ceramic

Flat Tile/Plate, ceramic

White ceramic glazed top 150 x 150mm. Supplied in a pack of 5.

TJ998-30 Flat tile, ceramic

Ceramic Plates for bench protection – see *Mats section*.

Microtest and Multiwell Plates – see *Tissue Culture and Microtitration sections*.

Support Plates for use with retort stands – see *Stands section*.

Mats

Mats, ceramic fibre

Provide heat protection to benches. An alternative to asbestos bench mats. Approximately 5mm thick. Supplied singly.

	Size, mm
MB800-15	150 x 150
MB800-22	225 x 225
MB800-30	300 x 300

Mats, PTFE

5mm thick, white PTFE. Operating temperature range -200°C to +250°C. Note: DO NOT EXPOSE TO DIRECT HEAT. Supplied singly.

	Size, mm
MB810-25	150 x 150

Mats, Ceran®

Ceran® is a highly resistant, glass ceramic material. Operating temperature range -200 to +700°C, allowing the mat to be used as a heating surface in place of a wire gauze or fireclay triangle. Care should be taken to ensure that the maximum operating temperature is not exceeded when using with a Bunsen burner. Supplied in packs of 10.

	Size, mm
MB820-10	135 x 135
MB820-20	155 x 155
MB820-30	175 x 175

Ceran® is a registered trade mark of Schott Glaswerk.

Bench Protection Sheets – see *Safety section*.



TJ995-10



TJ995-25



TJ998-30



MB800



MB810



MB820 in use