

Timers

Stopwatches

| Cat. No. | TM400-05 | TM480-12 | TM480-23 | TM485-32 |
|---------------|----------------|------------|------------|------------|
| Type | Mechanical | Electronic | Electronic | Electronic |
| Movement | Standard lever | — | — | — |
| Jewels | 13 | — | — | — |
| Hours | — | 23 | 23 | 10 |
| Minutes | 30 | 59 | 59 | 59 |
| Seconds | 0.2 | 59 | 59 | 59.99 |
| Side flyback | ✓ | — | — | — |
| Split | — | ✓ | ✓ | ✓ |
| Day/Date/Time | — | ✓ | ✓ | ✓ |

Mechanical Stopwatch

As described. 13 jewel standard lever mechanism. Stainless steel case with centre crown stop/start and side flyback.

TM400-05 Mechanical stopwatch, 30 minutes x 0.2 seconds

Electronic Stopwatches

As described. Quartz controlled movement, 24 hour models with liquid crystal display in robust plastic cases. Split time facility count to 0.01 seconds for first 30 (TM480-21) or 40 (TM480-12, -23) minutes and then in 1 second increments to 24 hours. Include time/calendar display mode and alarm. With battery. TM480-12, -21 and -23 are additionally supplied in a water resistant case.

TM480-12 With 8mm high display

TM480-23 With 12mm high display

BL590-25 Battery, 3V, spare for TM480-series

Water Resistant, Electronic Stopwatch

As described. Water Resistant Electronic Stopwatch, 10 Hour X 0.01Sec. 8mm high display, with lap and split timing, 999 lap & 300 memories, with fastest, slowest and average speeds, countdown timer and pacer functions, clock with calendar & alarm. Supplied with battery.

TM485-32 Water resistant, electronic stopwatch

BL590-25 Battery, 3V, spare for TM485-32

Time Switch and Wall Clocks

Time Switch

With integral 13A 3-pin plug and socket fitting for connecting directly to the mains supply and to equipment being controlled. Large dial with simple time setting by switch pins. Overall 70 x 70 x 33mm deep.

Minimum setting interval

15 minutes

Minimum time period

30 minutes

For 230V 50Hz single phase supplies. Maximum rating 13A.

TM850-20 24 hour

Wall Clock, analogue

Quartz mechanism, battery operated. White moulded plastic case with 254mm diameter, 12 hour dial with sweep second hand. Overall diameter 270mm. With battery and integral wall mounting bracket.

TM900-12 Wall clock, analogue

BL610-15 Spare battery 1.5V

Wall Clock, analogue, with hygrometer and thermometer

Quartz mechanism, battery operated. Moulded plastic case finished in silver with 280mm diameter, 12 hour dial with sweep second hand and subsidiary dial hygrometer (0 to 100%RH) and thermometer (-24 to +54°C). With battery and integral wall mounting bracket.

TM900-30 Wall clock/hygrometer/thermometer

BL610-15 Spare battery 1.5V



TM400-05



TM485-32



TM850-20



TM900-12



TM480-12



TM480-23



TM900-30