

Tubing Accessories

Tubing Accessories

Clamps

With non-slip serrated wheel and sloped floor which allow variable flow regulation. Plastic. Can be autoclaved up to 134°C.

	Ref.	Max. tubing o.d. mm
TY900-20	KT4.5	4.5
TY900-25	KT6	6
TY900-30	KT10	10
TY900-40	KT14	14

Tubing Cutter

For normal wall rubber and plastic flexible tubing up to 19mm o.d. With spring loaded hardened steel blade which is covered when the cutter is not in use.

TY915-20	Cutter
TY917-18	Spare blade

Non-return valve – see PX185.

Tubing adapters – see AD100/AD220.

Clips/Clamps

Providing shut-off or flow control for flexible tubing.

	Type	Max. tubing dia. mm	Material
CP100-15	Mohr	10	Nickel plated alloy
CP100-19		12	
CP103-10	Ratchet	10	Polypropylene
CP106-08	Centre hinged, spring	8	Stainless steel and acetal
CP106-10		10	
CP109-10	'Stop-it', bottom hinged	10	PVDF and zinc plated steel
CP109-15		15	
CP109-20		20	
CP114-25	Hoffman, bottom hinged, light	25	Nickel plated brass
CP114-30		30	
CP114-40		40	
CP115-40	Hoffman, bottom hinged	40	Nickel plated brass
CP120-14	Hoffman, side hinged	14	Acetal



TY900 in use



CP103



CP106



CP120



TY915 in use



CP109



CP114



CP100



CP115