

Ultrasonic Cleaners

Digital Ultrasonic Cleaning Baths



- ◆ Stainless steel tank with rugged, industrial plastics housing
- ◆ Tank capacities 2.50 to 25.00 litres
- ◆ Combined frequency sweep and Leap-and-degas ultrasonics ensure superior cleaning activity and results
- ◆ Digital setting and readout of timer and heating
- ◆ Heating range ambient +5°C to +70°C
- ◆ Built-in SD Flash memory card slot enables storage and download of procedural records to the user's PC
- ◆ Easily accessible tank drain included
- ◆ Supplied with stainless steel basket and tight-fitting, ABS lid

Specifications:-

Catalogue No.		UL325-25	UL325-30	UL325-35	UL325-40	UL325-45
Model		QS5	QS10	QS12	QS18	QS25
Capacity,	litres	4.50	9.50	12.50	17.50	25.00
Peak power,	W	100	200	200	300	400
Heater	°C	Ambient +5 to +70 — all models				
Timer		0 to 99 minutes — all models				
Bath dimensions*	mm					
Internal	D	150 (267)	150 (267)	200 (366)	200 (366)	200 (366)
(External)	L	300 (345)	500 (350)	295 (345)	330 (374)	500 (551)
	W	150 (200)	150 (183)	245 (288)	300 (347)	300 (347)
Weight	kg	5.6	8.5	10	13	17

*All dimensions are nominal. All tanks have radiused corners.

Digital Ultrasonic Baths, Ultrawave

As described. Supplied with tight-fitting ABS lid, stainless steel basket, SD memory card slot and drain. For 230V 50/60Hz single phase supplies. Supplied without SD memory card.

- UL325-25** Model QS5
- UL325-30** Model QS10
- UL325-35** Model QS12
- UL325-40** Model QS18
- UL325-45** Model QS25

Note:

Items to be cleaned should not be allowed to rest on the bottom of the tank during operation. The use of an accessory basket is recommended to avoid this.



UL325-15



UL325-25